

ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.



SMART DESIGNS COME FROM SMART SOLUTIONS.



NESTAFLEX®  
FLEXIBLE CONVEYORS

226

GRAVITY SKATE WHEEL CONVEYOR



Designed to expand, contract and move easily, the **226** is a self tracking, gravity skate wheel conveyor that has a per liner foot capacity of 226 pounds! This unit is engineered to handle multi-sized cartons in low to medium volume applications.

The **ALL-STEEL** construction provides unmatched structural integrity, whether the conveyor is extended, compacted or configured in simple or compound curves. Adjustable inner legs vary height to achieve gravity flow. The **NESTAFLEX 226** is the choice for use in retail store level applications, packaging areas, assembly lines and

in low volume shipping and receiving departments. Call us today to learn more at 800.669.1501 or visit our website at [www.flexmh.com](http://www.flexmh.com).



CONVEYOR OPTIONS



Dockless Receiving



Swing Stick



T-Junction



Flexible Side Rails



SMART DESIGNS COME FROM SMART SOLUTIONS.

## SPECIFICATIONS

14" WIDTHS		18" WIDTHS		24" WIDTHS		LENGTH ADJUSTMENTS WITH 5 1/4" AXLE CENTERS		
Model 226	*Skate Wheels Per Axle	Model 226	Skate Wheels Per Axle	Model 226	**Skate Wheels Per Axle	Contracted/Extended	Leg Sets Per Unit	Bed Sections Per Unit
22614008	6	22618008	6	22624008	8	2' 4" - 8' 11"	3	2
22614012	6	22618012	6	22624012	8	3' 3" - 12' 10"	4	3
22614016	6	22618016	6	22624016	8	4' 3" - 16' 9"	5	4
22614020	6	22618020	6	22624020	8	5' 2" - 20' 9"	6	5
22614024	6	22618024	6	22624024	8	6' 2" - 24' 8"	7	6
22614028	6	22618028	6	22624028	8	7' 1" - 28' 7"	8	7
22614032	6	22618032	6	22624032	8	8' 1" - 32' 6"	9	8
22614036	6	22618036	6	22624036	8	9' 0" - 36' 5"	10	9
22614040	6	22618040	6	22624040	8	10' 0" - 40' 5"	11	10
22614044	6	22618044	6	22624044	8	10' 11" - 44' 4"	12	11
22614048	6	22618048	6	22624048	8	11' 11" - 48' 3"	13	12
22614052	6	22618052	6	22624052	8	12' 10" - 52' 3"	14	13
22614056	6	22618056	6	22624056	8	13' 10" - 56' 2"	15	14
22614060	6	22618060	6	22624060	8	14' 9" - 60' 1"	16	15

\*8 Skate-wheel option available on 14" wide models    \*\*10 skate wheel option available on 24" wide models

## NESTAFLEX 226 STANDARD FEATURES AND OPTIONS

NESTAFLEX  
STEEL CONVEYORS

# 226

### SKATE WHEEL OPTIONS



N-Red Nylon



P-Black Polymer



S-Steel

### CONSTRUCTION

All steel construction.

### CONVEYOR FORMATS

Available in 14", 18" and 24" widths. Lengths can be tailored to your specific application.

### SKATE WHEEL OPTIONS

N-Red Nylon with nylon bushing for high-impact, short conveyors runs.

P-Black Polymer with 7 steel ball bearings in a captive race provides superior wheel rotation.

S-Steel skate wheel with steel ball bearings for impact resistant, moderate to high volume usage.

### HEIGHT ADJUSTMENT

Standard adjustable heights from 28" to 44". Other height adjustments available.

### LEGS

Zinc plated, heavy duty leg supports 1 1/8", square steel tubing and feature a welded cross member for added strength.

### HEAVY DUTY CASTERS

Standard 5" x 1 1/2" swivel casters with steel brakes.

### SIDE LINKS

Conveyor side links are made of 11 gauge steel.

### COUPLERS

Couplers are standard. Optional universal connectors are available to couple to other extendable conveyor brands.

### BOX STOP/HANDLE

Retractable package stop serves also as an ergonomic handle.

### AXLES

5/16" diameter axles. Standard axle centers are 5 1/4", 4" and 3" are available for smaller cartons.

### WARRANTY

18 month factory warranty.